

# 16 Gauge by RediFrame

Shown with  
standard  
wood casing

RediFrame® steel frames have been chosen to outfit hospitality, multifamily, condominiums, office buildings, and assisted living facilities. The diversity is in our design. RediFrame is engineered to adapt to a variety of commercial and residential applications. Designed for Cased Opening, Single, Pair, Communicating, Dutch, and Double Egress... try RediFrame first for special openings. RediFrame is prefinished and can be specified to fit the hardware for any job. And, because we can prefinish, it installs over finished walls, creating a perfect jobsite finish.

## Installation

The success of RediFrame® lies in the ease of installation, saving time and money. **RediFrame® is pre-finished, so installation occurs AFTER the wall is finished.**

## Innovation

Dunbarton's continuing innovation has produced an adjustable strike, a patented casing corner bracket, and the Universal Hinge Prep, S56 safety guard emboss, heavy hinge prep, and an ABH 1000 / GJ100 series concealed overhead holder and stop. **We offer over 26 different electric strike preps, and 10 different concealed closure options.**

## Security\*

RediFrame® is designed to sleeve the wall, becoming an integral part of the wall system. In comparative impact testing 18 ga. RediFrame® withstood 850 impacts, over 500 more than hollow metal. The difference is the anchoring system. Not only does **RediFrame® sleeve the wall, but it anchors to the wall using at least 30 fasteners.**

## Durability\*

RediFrame® carries a Certification of Level A 1,000,000 cycles (ANSI 250.5-1994).

## Testing

RediFrame® pledges to stay ahead of the field when it comes to fire ratings. We have taken the initiative to pass the most stringent and difficult tests to acquire the Warnock **Hersey standard in both neutral (UL 10B) and positive (UL 10C) pressure fire ratings.**

*\*Test results available upon request.*

## RediFrame® 16 Gauge Standard Options:

- A-40 galvanized only
- 1-3/4" & 1-3/8" doors
- 17 standard wall sizes
- Custom profiles: 2-5/8" to 15"
- 5/8" stop height
- Demountable without damage to the finished wall, door or frame
- Standard casing is wood trim by others
- Steel, S56, & aluminum casing available with field installed clips
- Welded 3-1/2", 4" & 4-1/2" hinges
- Welded 2-3/4" & 4-7/8" strike prep
- Mylar 90 minute neutral and positive pressure fire label; wood or steel stu

**DUNBARTON  
CORPORATION**  
*Your Complete Opening Solution*

# REDIFRAME

1101 Technology Drive  
**800.633.7553**  
www.dunbarton.com

| Dothan, Alabama 36303  
| 334.794.9184 fax  
| sales@dunbarton.com



**Scan to go directly  
to RediFrame  
product webpage!**